

Appl. No. 10/729,594
Request for Continued Examination
Reissue of U.S. Patent No. 6,325,294 B2
Att. Dkt. M40-367

In the Claims

Claim 7 is amended as follows:

7. (Once Amended) A data storing device comprising:

a housing defined by first and second housing portions, the second housing portion being movable relative to the first housing portion between mated and open positions;

an integrated circuit supported by the first housing portion;

a battery in the housing; [and]

a conductor supported by and movable with the second housing portion, the conductor coupling the battery to the integrated circuit when the second housing portion is in the mated position; and

wherein the first and second housing portions enclose and hermetically seal the integrated circuit and the battery when the first and second housing portions are in the mated position.

Claim 16 (cancelled).

Claim 19 is amended as follows:

19. (Twice Amended) A portable data storing device comprising:

a housing defined by first and second housing portions each including planar surfaces;

an integrated circuit including a static random access memory configured to store the data, the integrated circuit being supported from the first housing portion;

Appl. No. 10/729,594
Request for Continued Examination
Reissue of U.S. Patent No. 6,325,294 B2
Atty. Dkt. M140-367

a thin film battery in the housing; [and]

a conductor supported by and movable with the second housing portion, the conductor coupling the battery to the integrated circuit so that the integrated circuit is powered by the battery when the first and second portions are mated and thereby resulting in the static random access memory being powered by the battery and so that the integrated circuit is not powered by the battery when the first and second portions are not mated; and

wherein the conductor completes a circuit and supplies electrical power to the integrated circuit when the first and second portions of the housing are sealed together and does not complete the circuit or supply the electrical power to the integrated circuit when the first and second portions are not sealed together.

Appl. No. 10/729,594
Request for Continued Examination
Reissue of U.S. Patent No. 6,325,294 B2
Atty. Dkt. M140-367

Please add new claims as follows:

25. (Once Amended) A portable data storing device comprising:

a housing defined by first and second housing portions each including planar surfaces;

an integrated circuit including a random access memory configured to store the data, the integrated circuit being supported from the first housing portion;

a thin film battery in the housing;

a conductor supported by and movable with the second housing portion, the conductor coupling the battery to the integrated circuit so that the integrated circuit is powered by the battery when the first and second portions are mated and thereby resulting in the memory being powered by the battery and so that the integrated circuit is not powered by the battery when the first and second portions are not mated; and

wherein the conductor completes a circuit and supplies electrical power to the integrated circuit when the first and second housing portions of the housing are sealed together and does not complete the circuit or supply electrical power to the integrated circuit when the first and second portions are not sealed together.

26. (Once Amended) A passive radio frequency identification device comprising:

a first flexible film having a peripheral portion;

a second flexible film laminated directly to the peripheral portion of the first flexible film;

a first dipole antenna disposed directly on the first film; and

Appl. No. 10/729,594
Request for Continued Examination
Reissue of U.S. Patent No. 6,325,294 B2
Atty. Dkt. M140-367

a single integrated circuit having substantially all circuitry formed on a surface of the integrated circuit facing the first film, the integrated circuit being coupled to the first dipole antenna and including memory to store an identification number, a receiver coupled to the first dipole antenna to receive and decode data from a spread spectrum signal in the range of approximately 200MHz to 10GHz, control logic to perform a comparison between the received data and at least a portion of the identification number, and a transmitter coupled to the first dipole antenna to transmit a response based on the comparison.

27. The radio frequency identification device of claim 26 further comprising an adhesive backing to affix the circuit to a surface.

28. The radio frequency identification device of claim 26, further comprising a second dipole antenna coupled to the integrated circuit and disposed between the first and second films, wherein the first and second dipole antennas are approximately perpendicular to each other in a generally X-shaped configuration.

29. The radio frequency identification device of claim 26, wherein the first dipole antenna comprises a printed conductive ink or epoxy.

30. The radio frequency identification device of claim 26, wherein only two terminals connect off-chip components to the integrated circuit.

Appl. No. 10/729,594
Request for Continued Examination
Reissue of U.S. Patent No. 6,325,294 B2
Atty. Dkt. M140-367

31. The radio frequency identification device of claim 26, further comprising a printed label adhered to the first flexible film.

32. The radio frequency identification device of claim 26, wherein the package is bar coded.

Claims 33-63 (cancelled).

64. The radio frequency identification device of claim 26, wherein the second flexible film has a peripheral portion which is laminated directly to the peripheral portion of the first flexible film to form an approximately hermetically sealed flexible package, and wherein the first dipole antenna is disposed between the first and second films, and wherein the single integrated circuit is disposed between the first and second films, and wherein the integrated circuit is coupled to the first dipole antenna using a conductive epoxy.